

UTICA[®] Solar MobileGrid 1000-1000



Flexible

- For systems from 500W to 5000W

- 1phase operation, connectable in parallel and modularly extendable

- AC and DC coupling

Simple

- Easy commissioning with the "Quick Configuration Guide"

- Complete off & on-grid management

Efficient

- High efficiency

- Intelligent battery management for maximum battery life

- Charge level calculation

Robust

- Extreme overload capability

- Proactive temperature management system

- 2-year warranty

Solar Powered Generator


UTICA[®] Solar MobileGrid is an off-grid solar power system that works 24-hours a day, powered by photovoltaic modules, complementing your existing energy consumption and hence, reducing electricity bills and carbon footprint.

The easy deployable system makes commissioning within minutes possible. All required operational settings can be made quickly and easily in just a few steps. The UTICA[®] MobileGrid is powerful, extendable and takes on all control processes.

Its first-class intelligent power processing unit ensures maximum battery life. It also features impressive efficiency, a rugged metal enclosure and active cooling system. With an output rating of 230V and 50 Hz, the UTICA[®] MobileGrid is designed perfect for any location.

Technical Data	MobileGrid 1000-1000
Solar panel	
Max power	1000W
Power/day	3500WH
AC output (Loads)	
Nominal AC voltage (adjustable)	230V
Nominal frequency (adjustable)	50HZ
Continuous AC power at 25 °C / 45 °C (77 °F / 113 °F)	1000 W
THD output voltage / power factor (cos φ)	<5%
AC input (generator or grid)	
AC input voltage (range)	230V
AC input frequency (range)	50HZ
Battery DC input	
Battery voltage (range)	24V
Max. battery charging current / continuous charging current at 25 °C (77 °F)	120 A / 100 A
Battery type	lead-acid battery
Capacity	24V,300Ah
Efficiency / operating consumption	
Max. efficiency	85%
Internal consumption with no load / standby	25 W / 4 W
Protection devices	
DC reverse polarity protection / DC fuse	●/●
AC short-circuit / AC overload	●/●
Overtemperature / excessive battery discharge	●/●
General data	
Inverter Dimensions (W / H / D) in mm (in)	400*428*88
Inverter Weight	15KG
Operating temperature range	-25 °C ... +50 °C (-13 ° F ... +122 °F)
Protection rating (as per IEC 60529)	indoors
Features / function	
Operation & display / multifunction relays	internal / 2
3-phase systems / parallel connection	●/●
Integrated bypass / multicluster operation	—/●
Charge level calculation / full- / equalization charge	●/●/●
Integrated soft start / generator support	●/●
Battery temperature sensor / communication cables	●/●
Warranty: 2 / 5 / 10 / 15 years	●/○/○/○/○
Certificates and permits	www.utica.sg
Accessories	
Battery cables / battery fuses	○/○
Interfaces (RS485 / Multicluster PB)	○/○
"GenMan" extended generator start	○
Load-shedding contactor / battery current measurement	○/○
● Standard features ○ Optional features — Not available	
Last revision: January 2013	
Remarks	System integrated controller & inverter, simply connect the solar panels and batteries to the system, the system can work, easy for use. Structure for inverter is low frequency, and that for controller is PWM.

- UTICA PV Mobile Grid 1000 Series**
- Assembled in Singapore
 - LED lights, radio, notebook, color TV and fans
 - System capacity 1000VA
 - Weatherproof for outdoor
 - Remote building sites
 - Inverter efficiency 85%
 - fast-charge power when you need it most
 - Portable and easy installation
 - AC & DC appliances anywhere
 - Maintenance-free battery as well as an indestructible outer case
 - Mini water pumps, wireless communication and computers



Solar Off-grid System

Hotline +65 6296 7787 Utica Singapore
www.utica.sg

